





Key Features

- Support GPS L1/L2 and GLONASS L1/L2 frequencies
- Multi-path rejection board inside can eliminate the multi-path influence to measurement error
- Adopt multi feed design to ensure the superposition of phase center and geometrical center, and minimize the influence to measurement error
- Very low noise figure
- GIS&RTK applications
- Mize size and lightweight
- 5/8" x 11 Mounting

Mini Survey Antenna HX-GS488A


HX-GS488A receives GPS L1/L2 and GLONASS L1/L2 frequencies, which can be used in land survey, marine survey, channel survey, seismic monitoring, bridge survey, container operation and agriculture applications. Customers can use the same antenna for GPS only or dual constellation applications.


It has high gain and wide beam width to ensure the signal receiving performance of satellite at low elevation angle. The phase center of this antenna remains constant as the azimuth and elevation angle of the satellites change. Signal reception is unaffected by the rotation of the antenna or satellite elevation, so placement and installation of the antenna can be completed with ease.


Technical Specifications

Antenna Specification	
Frequency Range	GPS L1/L2 GLONASS L1/L2
Impedance	50ohm
Polarization	RHCP
Axial Ratio	≤3dB
Azimuth Coverage	360°
Output VSWR	≤2.0
Peak Gain	5.5dBi
Phase Center Error	± 2 mm
LNA Specification	
LNA Gain	40±2dB
Noise Figure	≤2.0dB

Output VSWR	≤2.0	
Operation Voltage	3.3~12VDC	
Operation Current	≤45mA	
	-	
Group Delay	≤5ns	
Mechanical Specification		
Dimension	φ 152*62.2mm	
Connector	TNC Female	
Weight	374g	
Environment Specification		
Storage Temp	-45℃~+85℃	
Operating Temp	-55°C∼+85°C	
Humidity	059/	
	95%	
	No-condensing	







Side view

Bottom view

Dimension (mm)

Harxon Corporation





